

RubberCover™ QuickSeam Pipe Flashing

1. Description

Firestone's QuickSeam Pipe Flashing is specifically designed to be used for flashing of rigid round penetrations of 25 mm to 150 mm. It is a pre-fabricated pipe boot with a Quickseam tape laminated to the bottom of the flange of the boot. Each QuickSeam Pipe Flashing will fit various penetrations and shall be cut at correct pipe diameter before installation.

2. Preparation

Penetration must be clean of prior flashing and foreign materials. The RubberCover™ EPDM surface must be prepared with QuickPrime Plus, using a QuickScrubber tool. Use of other products is not allowed.

3. Application

Cut along the top edge of the ring on the QuickSeam Pipe Flashing corresponding to the size of the pipe. Install the pipe flashing and clamping ring per Firestone specifications and details.

4. Coverage

1 piece per penetration.

5. Characteristics

Technical	Moulded Pipe Flashing	QuickSeam Tape
■ Base	Moulded EPDM	Rubber polymer
■ Colour	Black	Black
■ State	Cured	Cured
■ Thickness	1.4 - 1.9 mm	0.76 mm
■ Flange diameter	330 mm	216 mm

6. Packaging / Storage / Shelf Life

Packaging: 10 pieces per carton. Stainless steel clamping rings are included.

Storage: Store in original unopened containers at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

Shelf Life: 12 months can be expected if stored in above-mentioned conditions. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories. Quality and applicability should thus always be verified: QuickSeam Pipe Flashing can be used only as long as the release paper can easily be removed from the tape without tearing the paper apart.

7. Precautions

Refer to Material Safety Data Sheet.

