

## RubberCover™ QuickSeam SA Flashing

### 1. Description

Firestone QuickSeam SA Flashing is a 457 mm wide RubberCover™ membrane fully laminated to Firestone QuickSeam Tape. It has a polyester release liner for easy removal and excellent weather resistance. The SA Flashing can be used to line gutters, carry out general roof repairs where cured EPDM is required, flash in drain insert pieces and pipe flanges.

### 2. Preparation

The RubberCover™ EPDM surfaces and/or mating surfaces must be prepared with QuickPrime Plus, using a QuickScrubber tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

### 3. Application

Refer to the Firestone specifications for specific installation instructions.

### 4. Coverage

In accordance with length of detail to be covered. Adjoining strips require an overlap of 25 mm and a cover patch.

### 5. Characteristics

<b>Physical</b>	<ul style="list-style-type: none"><li>■ Superior ozone and ultraviolet resistance.</li><li>■ Remains flexible over wide temperature variations.</li><li>■ Application temperature range is between -20°C and 50°C.</li><li>■ Outstanding adhesion to approved substrates for maximum performance.</li></ul>		
<b>Technical</b>		<b>EPDM Flashing</b>	<b>QuickSeam Tape</b>
	■ Base	EPDM	Rubber polymer
	■ Colour	Black	Black
	■ Solvents	None	None
	■ Solids	100 %	100 %
	■ State	Cured	Cured
	■ Thickness (mm)	1.52 mm	0.51 mm
	■ Width (mm)	457 mm	457 mm

### 6. Packaging / Storage / Shelf Life

**Packaging:** 15.25 m (50') rolls, 1 roll per carton.

**Storage:** Store in original unopened containers at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

**Shelf life:** 12 months can be expected if stored in above-mentioned conditions. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories. Quality and applicability should thus always be verified: QuickSeam SA Flashing Strip can be used only as long as the release paper can easily be removed from the tape.

### 7. Precautions

Refer to Material Safety Data Sheet.

